

INDOTAN SS

Special Amphoteric Polymeric Syntan

PHYSICAL PROPERTIES:

Composition	: Proprietary blend of vinyl polymers
Appearance	: Off whitish viscous flowing liquid
% Solids	: 48.0 – 49.0
pH (1:10)	: 3.4 – 5.0
Solubility	: Readily soluble in water

DESCRIPTION:

Indotan SS is versatile polymeric syntan for drum impregnation of splits, full grain and corrected grain leathers. It can be used in rechroming along with chrome. It improves the roundness & compactness of leather fibers resultant in short nap in buffing which are very important for suede and nubucks.

Indotan SS imparts following unique properties,

- Gives excellent filling properties with smooth grain
- Improves buffing properties to great extent
- Imparts compactness to fibers and reduces the stretchiness
- Gives short nap in buffing for nubucks and suedes
- Compatible with retannage and fatliquors
- Recommended to use in rechroming along with chrome
- It can be added after fatliquoring for short nap
- No bleaching effect in dyeing

APPLICATIONS:

Indotan SS is suitable for all types of leathers such as shoe uppers, softies, split uppers & all types of corrected grain leathers where compact grain and good buffing properties are essential.

Indotan SS is having wide range of applications as follows,

- For cow & buff calf nubuck : 1.0 – 3.0% after fatliquoring
- For buff crazy horse : 2.0 – 3.0% after fatliquoring
- For splits shoe suede : 2.0 – 3.0% after fatliquoring

STORAGE STABILITY:

6-9 months if properly stored in cool & dry place under shed in sealed drums.