

Provisional Literature

INDOFIL OIL UR 0715

Specialty High Lightfast Fatliquor

Indofil Oil UR 0715 is anionic synthetic fatliquor with good softness with good light fastness & heat resistance. It penetrates well and suitable for soft & tight leathers.

PHYSICAL PROPERTIES:

- Composition : Sulphoesters with specialty additives.
- Appearance : Yellow to reddish brown clear viscous liquid.
- pH (1:10) : 7.0 – 9.0
- Stability of Emulsion: Stable to mild acids, hard water & electrolytes.

DISCRIPTION:

Indofil Oil UR 0715 is anionic lightfast synthetic fatliquor especially designed for all Shoe uppers, softies, garment nappa, gloving and milled leathers. It imparts excellent light fastness & capacity to penetrate & drive all other fatliquors throughout the cross section with light weight.

Indofil Oil UR 0715 imparts following unique characteristics,

- Anionic penetrative fatliquor.
- Imparts good softness with light weight.
- Imparts silky surface touch & warm handle.
- Lightfast & heat resistant so suitable for white & pastel shades.
- Helps in uniform distribution of retanning agents and fatliquors.
- Compatible with all retannage, vegetable extracts & fatliquors.
- Stable in rechroming

- No bleaching effect

APPLICATION:

Indofil Oil UR 0715 is to be added to the drum by pre dissolving with other fatliquors & water. It is recommended for all types of full grain, corrected grain uppers, suede, nubucks, gloving and milled articles

Indofil Oil UR 0715 is having wide range of applications as follows,

For Cow/Buff full grain & corrected grain	: 2% – 6% in fatliquoring
For nappa and gloving leathers	: 4% – 10% in fatliquoring
For suede & nubuck leathers	: 3% – 6% in fatliquoring
In Rechroming	: 1% - 4% in Rechroming

STORAGE STABILITY: 6-9 months if properly stored in cool & dry place under shed in sealed drums. It is recommended to stir well the product before each & every use.

Technical Suggestions are without any obligations

Prepared on 18-09-2015

(IIL/SPCD/Leather/Sept 2015/UR 0715/Rev 0)